

PRIMO SAFE.T

TECHNICAL DATA

CERTIFICATION & CLASSIFICATION	STANDARDS	PRIMO SAFE.T
Type of floor covering	EN 13845	Slip resistant homogeneous vinyl flooring
Classification	EN ISO 10874	Commercial: 34 Industrial: 43
TECHNICAL CHARACTERISTICS		
Total thickness	EN ISO 24346	2.0 mm
Total weight	EN ISO 23997	3000 g/m ²
Surface treatment		Safe.T clean XP™
Form of delivery	EN ISO 24341 Sheet (rolls)	Approx. 23 lm x 200 cm Art. no. 21013 _ _ _ 3 digit colour number
PERFORMANCES FOR CE MARKING REQUIREMENTS (EN 14041)		
Declaration of Performance	EN 14041	0019-0048-DoP-2013-07
Reaction to fire	EN 13501-1	Class B _{fl} -s1
	EN ISO 9239-1	≥ 8 kW/m ²
	EN ISO 11925-2	Pass
Electrostatic properties	EN 1815	< 2 kV
Thermal resistance	EN 12667/DIN 52612	Approx. 0.01 m ² K/W
Slip resistance	EN 13893 /BS 7976-2	≥ 0.3 / Low risk of slip
TECHNICAL PERFORMANCES		
Residual indentation	EN ISO 24343-1	Required value: ≤ 0.10 mm Best measured value*: 0.03 mm
Slip resistance	DIN 51130	R10
Bacteria resistance	EN ISO 846: Part C	Does not favour growth
Chemical resistance	ISO 26987	Good resistance
Castor chair	ISO 4918	Suitable
Flexibility	ISO 24344	Pass
Dimensional stability	EN ISO 23999	≤ 0.40 %
Light fastness	EN ISO 105-B02	≥ 6
Bare foot test	DIN 51097	Class B (≥ 18°)
Seam strength	EN 684	Individual values: ≥ 400 N/50 mm
Underfloor heating		Suitable - max. 27°C
ENVIRONMENTAL PERFORMANCES		
Total VOC emissions	ISO 16000-9 / Indoor air quality	≤ 10 µg/m ³ (after 28 days) / Platinum
COLOURS		

15

The above information is subject to modification for the benefit of further improvement. (04/18).

*For information - not binding.

According to the European Regulation N° 305/2011 for CE Marking, the Declarations of Performance are available on our website www.tarkett.com

Tarkett's instructions regarding installation, cleaning and maintenance should be observed. Please contact Tarkett at the address shown for these instructions.

Colours of the products shown in the photos or samples are indicative only. There may be differences in colours, gloss and embossing structure between the products sold and photos or samples.

CUSTOMS TARIFF : 4820 5000 00



PRIMO SAFE.T

Article	Colour name	WR (Multi)
21013790	lt pure grey	1290369
21013791	md pure grey	1290284
21013792	md grey	1290285
21013793	lt warm grey	1290286
21013794	md cool grey	1290287
21013795	dk cool grey	1290288
21013796	lt cool beige	1290289
21013797	md cool beige	1290290
21013798	dk cool beige	1290291
21013800	md warm-beige	1290293
21013801	dk warm-beige	1290368
21013802	lt green	1290295
21013803	md green	1290296
21013805	lt blue	1290370
21013806	md blue	1290299